



US009410759B2

(12) **United States Patent**
Smith, Jr.

(10) **Patent No.:** **US 9,410,759 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **BURST FIRING DEVICE FOR FIREARM**

(56) **References Cited**

(71) Applicant: **Michael S. Smith, Jr.**, St. Augustine, FL
(US)

(72) Inventor: **Michael S. Smith, Jr.**, St. Augustine, FL
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/682,426**

(22) Filed: **Apr. 9, 2015**

(65) **Prior Publication Data**

US 2016/0202010 A1 Jul. 14, 2016

Related U.S. Application Data

(60) Provisional application No. 62/103,394, filed on Jan.
14, 2015.

(51) **Int. Cl.**
F41A 19/59 (2006.01)
F41A 19/10 (2006.01)
F41A 19/12 (2006.01)
F41A 19/14 (2006.01)

(52) **U.S. Cl.**
CPC **F41A 19/10** (2013.01); **F41A 19/12**
(2013.01); **F41A 19/14** (2013.01)

(58) **Field of Classification Search**
CPC F41A 19/69; F41A 19/02; F41A 19/06;
F41A 19/58; F41A 17/06
USPC 42/69.01; 89/128–131
See application file for complete search history.

U.S. PATENT DOCUMENTS

3,292,492 A * 12/1966 Sturtevant F41A 17/46
89/128
3,774,500 A * 11/1973 Into F41A 19/02
89/129.01
4,004,496 A * 1/1977 Snodgrass F41A 19/02
89/129.02
4,510,844 A * 4/1985 Fritz F41A 19/62
89/129.02
7,878,106 B2 * 2/2011 Hu F41A 19/02
89/129.02
8,807,007 B2 * 8/2014 Alicea F41A 17/06
89/28.1
9,151,559 B2 * 10/2015 Alicea, Jr. F41A 17/06
2010/0186277 A1 * 7/2010 Beckmann F41A 19/69
42/69.01
2013/0118050 A1 * 5/2013 Alicea F41A 17/06
42/84
2015/0241156 A1 * 8/2015 Alicea, Jr. F41A 17/06
89/28.1

* cited by examiner

Primary Examiner — Michael David

(74) *Attorney, Agent, or Firm* — Dunlap Bennett & Ludwig
PLLC

(57) **ABSTRACT**

A burst firing trigger mechanism is provided. The mechanism includes a sear having a hamper engagement surface and a transfer mechanism. The present invention further includes a plurality of triggers. The plurality of triggers each includes a lever, a base pivotally attached to the sear by a pivot pin, and a trip finger extending from the base. Each of the trip fingers extends at a different angle relative to the lever. The present invention further includes a hammer biased by a spring away from the sear. The hammer includes a cocking notch. The burst firing trigger mechanism includes a cocked position and a plurality of fired positions. The cocked position includes the hammer engagement surface engaging the cocking notch and suspending the hammer towards the sear. Each of the plurality of fired positions includes the plurality of triggers pivoted so that at least one of the trip fingers engages the transfer mechanism thereby disengaging the hammer engagement surface from the cocking notch and thereby releasing the hammer.

8 Claims, 8 Drawing Sheets

